



JTI manufacture an extensive range of server racks in heavy arade aluminum profiles that are powder coated in black color. The steel doors and side also covers are powder coated black color.

JTI Server CoolRack - Front view with fully perforated steel door and front/back cable management facility

Better thermal management is possible as incoming cold air is not allowed to mix with hot air being exhausted from rack using high suction exhaust fans at the top. As the rear and both sides of rack are completely closed to prevent air leakages and cold air enter the rack through front perforated door, which forces cool air to pass through servers.

Key Features

- Standard 19" server Rack
- Front steel doors fully perforated
- Rear plain steel door
- Top cover with high suction 2500 RPM and total 1500 CFM fans
- Cable entry provision from top and bottom
- Plain side panels with slam latches
- Adjustable 19" mounting angles at front and rear
- Front and back cable management facility
- Completely knock down (CKD) design for easy transportation and assembly
- Load rating 1500 kg with base frame

Jyotitech Industries

R-607, TTC Industrial Area, Thane Belapur Road, Rabale, Navi Mumbai - 400701

Tel: +91-22-27696631 Fax:+91-22-27696632

Email:sales@jyotitech.com Website:www.jyotitech.com

Page

JTI Server CoolRack (Aluminium Profile)

2012

Size

Height: 42UWidth: 600 mmDepth: 1200 mm

Material and Finish

- The frame is made of heavy duty aluminum extrusions
- All Black

Benefit

The advantage of this rack is cool air (Precision AC) is utilized optimally thereby reducing running cost

Basic Requirements

- Precision AC and raised floor
- False ceiling with clear return air path from rack to Precision AC

Floor Standing Rack Model Matrix Dimension

 \rightarrow 1U = 44.45 mm

Note: Other models can be manufactured on request The dimensions may vary with changes in the rack design

JTI Floor Standing Racks 600W (19") Dimension Matrix						
JTI (600 W Floor	Overall	Usable	Overall	Usable	Overall	
Standing Rack Series)	height	height	width	width	depth	Usable depth
42U/600/1200	2023.9 + top fan duct 250-480 adjustable + base frame 100	1866.9	600	450	1200	810 + front channel 125 + back channel 200

Jyotitech Industries

R-607, TTC Industrial Area, Thane Belapur Road, Rabale, Navi Mumbai - 400701

Tel: +91-22-27696631 Fax:+91-22-27696632

Email:sales@jyotitech.com Website:www.jyotitech.com

Page